


We'll help you meet the challenge of finding unique solutions to your most critical problems

## DPH5 Tantalum Lead Seal



COMPOSITION	
Thickness (mm)	0.129
Thickness Tolerance (mm)	±0.019
Fluoropolymer Thickness (mm)	0.013
Meltable Fluoropolymer Thickness (mm)	0.13
Total Substance Weight (g/m <sup>2</sup> )	298
PROPERTIES	
Color	Cream
Melt Temperature (°C)	302-310



Tests to determine application suitability should be made by each user.  
Electrolock can not guarantee performance in the user's application.  
Copyright 2014 Electrolock, Incorporated.  
Electrolock, Inc. is an ISO-9001-2008 certified company.



[www.electrolock.com](http://www.electrolock.com)

### > Description

DPH5 Tantalum Lead Seal is a unique two-sided fluoropolymer film engineered to assure a highly reliable anode seal in surface mount tantalum capacitors. The thin film thickness punches easily allowing capacitor manufacturers to form small diameter washers with a very low thickness profile. DPH5 lead seal washers position easily and resist distortion during the oxidation.

### > Availability

DPH5 is supplied in 10mm wide rolls but can be slit to your required width in wide variety of put ups.

### > For more information

For more information on this product or any other fine Electrolock products, please contact your nearest sales representative.

### > In Asia & China, contact:

**Admat Incorporated**  
[www.admatinc.com/contactus](http://www.admatinc.com/contactus)  
+1 (484) 322-2090